

CONFERENCE HOST WITH RECORD AES67R



Product Description

CONFERENCE HOST AES67R

Host function

Comply with IEC60914, GBT15381-94 international standards;

- *The panel has a USB recording interface, plug in the U disk to record

- *The system host can intelligently identify delegates and chairmen without assigning IP address I.

- *Anti-interference circuit design to eliminate all interference of mobile phone signals;

- *Clear sound, high fidelity, low noise interference, strong confidentiality, and easy installation;

- *The system has electronic volume control for each output and input adjustment function

- *Built-in AC and DC channel double fuses, automatic power-off protection when overcurrent

- *★It has 4-way RJ45 microphone unit interface, and supports hot-plugging of microphone units, each channel supports 20 units, and 60 units can be connected

- ★At the same time, it has 4-channel 8-core microphone unit interface, each channel supports 30 units, and 120 units can be connected

With 2.8-inch display menu, conference function control is realized through six function buttons

- *The number of chairpersons can be up to 12 chairperson units, and the number of speakers can be set arbitrarily from 1 to 12

It has a variety of conference modes: full-open discussion mode, number limit mode, first-in first-out mode, last-in-first-out mode, and chairman-only mode

- *The speaking time of the conference can be set between 0-99 seconds. After setting the time, the microphone will automatically turn off within a preset time.

- *It has the function of selecting the chairman's priority prompt sound. When the chairman presses the priority key, a prompt sound will be sent out.

- *Conference recording interface, with multiple audio input and output ports.

It has a central control RS-232 interface, which can be connected to third-party equipment control functions. .