

Sub Bass LS18



LS18

Feature Ls18 uses an 18-inch long coaxial drive neodymium magnet 100-core unit speaker. The LS18 can be perfectly combined with the PS15 speaker to form a complete sound system. The LS18 is composed of 18mm thick imported multi-layer plywood. The cabinet itself has a strong Tensile strength. There is a dedicated support base on the surface of the speaker, which can be used in conjunction with speakers with the same support base.

SPECIFICATIONS

Frequency Response [a]	35 Hz - 120 Hz \pm 3dB
Usable Range @-6dB [a]	32Hz - 130 Hz
Sensitivity 1W @ 1m [b]	107 dB SPL Nominal
Nominal Peak SPL @ 1m [b]	137 to 140 dB Peak
Nominal Impedance	8 Ω
Crossover Frequencies	60 Hz – 85 Hz - 120 Hz Active
Amplified Controller	NXAMP4x1: 2 x LS18 in parallel on 2 bridged channels NXAMP4x4: 2 x LS18 on 1 channel

FEATURES

Components	1 x 18" (46cm) 4" voice coil long excursion 8 Ω driver
Height x Width x Depth	510 x 675 x 775 mm (20.1" x 26.1" x 30.5")
Weight : Net	55.5 kg (122.3 lb)
Connectors	2 x NL4MP Speakon 4 pole
Construction	Baltic Birch Ply & structured black coating
Handles	4 metal recessed pockets (2 per side)
Front finish	Molded Dark Grey Metal Grill
Flying Points	Two side plates connecting with external accessories
Stand fittings	Internal Steel Stand Fitting on Top (35mm, 1"3/8) allows pole mounting for PS15 or Geo S12