Professional Audio Digital Mixer T-20



Product DescriptionDigital Audio Mixer t20 with 20 Channels, USB Audio Interface, Built-in Effects, 17 Moving Faders, iPad Controllability, and Touchscreen

1:20 Signal Input (16 MIC Input and 1 Stereo Input)

2:10 Signal Output (Main Output L, R, 4 AUX Output, 4 Marshalling Output)

3:+48V Phantom Power Supply (MIC Channel can be turned on and offindependently)

4: Each channel is equipped with 100MM electric push rod, signal and peaklamp (17 ALPS electric faders)

5: Built-in four-channel dual-DSP effector

6:7 inch 800*480 capacitive touch screen

7: Multi-Operating System Operating Software (IOS System, Android System, WINDOWS System)

8: User-defined layer, output mixed editing function

T20

Input sensitivity MIC:-60db LINE:-50db Maximum output voltage: 3V MAX Distortion (THD): < 0.03% (1KhzFull Power) Electronic gain: -32db to 10dB, 0.6~0.7 step. Input impedance: MIC > 5K; LINE > 10K Signal-to-noise ratio: > 85dB Frequency response: 20HZ-20KHZ+/-1db Parameter Equalization: input 5 segments (20HZ--20KHZ) + 12dB, Q0.3~15 adjustable Output parameter Equalization: output 15 segments (20HZ--20KHZ) + 12dB Q0.3~15 adjustable Output delay: 0-30ms Threshold, ratio: +6dB to -50dB Impact / release: 1--127ms Control: Network: Fast Ethernet (100Mb0/s) port can be connected to CAT5 cable.

A computer that controls mixer parameters over TCP / IP, or connects to a wireless router (access point) using IPAD or a T20 application on an Android phone for live mixing control, or connects to a Windows T20 control software interface.

Power supply: AC (250V-110V) /50-60HZ Professional effects Mod-FX Chorus, Flanger, Panning, Phaser, SineChorus, Tremolo, StepPhaser, Vibrato Reverb/Delay Spring65, Hall, CathedrL, DelayReverb1, Delay Reverb 2 Wah-Wah

```
DistortionType
"Tube1" "Tube2", "Tube3", "Hyperbolic", "Parabolic1".
Pitch-Shift
```

Length, Width and Height: 497 * 515 * 215MM (Length includes 6.35 input seats, Width includes side panel, Height includes foot; No knob)

Net weight: 9.69KG gross weight: 12.5KG packing size: 620*620*310MM