



The image displays two views of the VOSS P1000 amplifier. The top view shows the front panel, which features a digital display screen on the left showing '100.00' and '100.00'. To the right of the screen are seven frequency sliders labeled 'BASS', 'MIDLOW', 'MIDHIGH', 'TREBLE', 'BASS', 'TREBLE', and 'MID'. Further right is a 'POWER' button and a 'VOSS' logo. The bottom view shows the rear panel, which includes a power input jack, a power switch, a power fuse, and various output terminals for 'BASS', 'MID', and 'TREBLE'. It also features a 'VOSS' logo and a 'P1000' model number.

- IP Network Audio Decoder & Amplifier
- LAN / WAN / Internet-Based IP PA System
- Supports Up to 6,000 Paging Zones
- Multiple-Zone & Multiple-Program BGM
- Built-In 100V / 8Ω Amplifier
- Mic 1–3 & Line 1–2 Inputs
- 1 × Line Output
- 1 × Control Input & 2 × Control Outputs
- MP3 & Pre-Recorded Message Broadcasting
- Remote Volume & Program Control
- Scheduled Bell & Voice Message Broadcasting
- IP Paging Microphone Support
- Easy Installation Using Existing Network Infrastructure
- Ideal for Schools, Offices, Restaurants & Fitness Centres



OUR PRODUCTS

- 120W Rated Power Output
- Built-in IP Audio Decoder & Streaming
- TCP/IP, UDP & IGMP Protocol Support
- 10/100Mbps Network Transmission
- 16-bit Stereo CD-Quality Audio
- 20Hz–16kHz Frequency Response
- S/N Ratio: $\geq 85\text{dB}$
- THD: $\leq 0.3\%$
- 3 $\times$ Mic Inputs + 2 $\times$ Line Inputs
- 1 $\times$ Line Output
- 1 $\times$ Control Input + 2 $\times$ Control Outputs
- 100V / 70V & 4–16 Ω Speaker Output
- LAN / WAN / Internet-Based IP PA System
- Remote Volume & Program Control
- AC 220V, 50–60Hz
- Dimensions: 484 $\times$ 366 $\times$ 88mm
- Weight: 11.5kg