

VOSS AUDIO EX16-8 STAGE BOX



Product parameters

- 18 signal input (16 MIC/Line input 1 group Digital input: optical fiber/sound card, MP3)
- 10-channel signal output (10-channel group output + 1-channel monitor output + 1-channel optical fiber output)
- Input channel pan adjustment
- Built-in feedback suppressor
- AutoMixer function
- MIC input gain adjustment (digital gain)
- +48V phantom power (MIC channels can be turned on and off independently)
- Each input channel has built-in noise gate, compressor, high and low pass, input 5-band parametric equalization, delay, channel panning balance adjustment
- Channel parameter quick copy function
- Input and output EQ ON/OFF
- Multi-function knob, direction keys
- Multi-function menu for each channel, mute and monitor
- 10 signal outputs
- Processing per output channel: high and low pass filtering, 11-band parametric EQ, compressor, delay, phase
- Digital recording function
- Double row 3-color 12-segment level indicator
- Built-in sound card (mobile phone, IPAD, MP3, PC direct playback, recording)
- 4 quick scene recall modes, 20 scene storage
- Storage and recall of user parameters (can be managed on PC)
- Built-in two independent DSP effects
- Optical input/output
- Multi-operating system control software (IOS system, Android system, WINDOWS system)
- Support wired network port adjustment (or wireless adjustment with external router)
- 4.3 inch 480*272 resistive touch display

Machine size/weight

Length, width and height: 480*330*90MM (length includes 6.35 input seat, width includes side plate, height includes machine feet; does not include knob)

Net weight: Gross weight: 6.2kg

Packing size: 550*370*150MM